



Specifications

3000T

Lightweight, compact and impressive traction makes this head the obvious choice for you who have a long-range crane carrier. Log Max 3000T is one of our smaller heads and is tailored for thinning.

Dimension and Weight

Weight	615 kg
Height	1325 mm
Width Roller Arms Open	1129 mm
Width Roller Arms Closed	964 mm

Felling and Cutting

Optional Saw Models	Saw 218 - 19cc, True-Cut 218 - 19cc, True-Cut 318 - 19cc, Saw 318 - 19cc
Optional Saw Tensioner	Automatic, manual
Top Saw Models	
Top Saw Tensioner	
Saw Oil Capacity	4 liters
Max Saw Bar Length	600 mm
Max Cut Capacity	516 mm

Delimbing

Number of Delimbing Knives	4
Max Delimbing Knife Opening	408 mm
Max Delimbing Full Coverage	326 mm

Feeding

Feed Roller Models	V-STEEL SOFT GRIP, V-STEEL HARD GRIP
Feed Roller Motors	398 cc

Max Feed Force	16.8 kN
Max Feed Speed	4.2 m/s
Max Feed Roller Opening	394 mm
Min Feed Roller Opening	12 mm

Hydraulics

Max Pressure	250 bar
Min Pressure	200 bar
Max Flow	200 l/min
Min Flow	140 l/min

Rotators

Rotators	Indexator AV12S, Indexator H152
----------	---------------------------------

Base machine

Excavator Max Weight	16 ton
Excavator Min Weight	12 ton
Wheeled Harvester Max Weight	20 ton
Wheeled Harvester Min Weight	13 ton
Tractor	ton
Crane Requirements Max	120 kNm
Crane Requirements Min	100 kNm

Control Systems

Control Systems	Log Mate 510
-----------------	--------------

* Standard and extra equipment are market-dependent and vary between countries. The specification describes possible equipment, not that which is standard or optional. Stated weights are based on standard equipment. Specifications and designs are subject to change without notice.